Wellmed Pro | Wellview Universal Group

TECHNICAL DATA SHEET

New Design Infant Radiant Warmer YSHKN-90

New Design Infant Radiant Warmer

Power requirement

AC220V-230V/50Hz or AC110-120V/50-60Hz, 600VA

Control Mode

Pre-warm Mode, Manual Mode and Baby Mode control by micro-computer

Baby Mode temperature control range

34.5-37.5℃

Skin temperature display range

5℃-65℃

Accuracy of skin temperature sensor

±0.2℃

Temperature uniformity of mattress

≤2℃

Angle of heater head

0°, 30°, 45°for two ways

Inclination of the bassinet

Five tilt position

Apra timer

Audible and visible alarm when the device runs to 50″~1′,4′50″~5′,9′50″~10′

Failure alarm

over temperature alarm, deviation alarm, sensor failure alarm, power failure alarm, setting alarm, checking alarm and so on.

Environmental Requirement

Operating range: 18 ℃~30℃

Ambient air velocity rate: <0.3m/s

Product Packaging

Package: The whole unit is packed into one carton

Dimension: 1110mm x 625mm x 1195mm

Gross Weight: 60kg

Product advantage of the Infant Radiant Warmer

- With a warm, hand control, skin temperature three kinds of temperature control mode;

- Set the temperature and skin temperature display;

- Independent over-temperature cut-off device of the triple over-temperature protection;
- Radiation box horizontal angle and the tilt angle adjustable crib;
- Products with self-test function, a variety of fault alarm;
- Cots can be placed under the X-ray film cassette.

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.