



Wellmed Pro | Wellview Universal Group

TECHNICAL DATA SHEET

YSX1002 Portable High Frequency Dental X-Ray Unit

Portable high-frequency dental x-ray unit

FUNCTION

The portable x-ray machine YSX1002 is a High Frequency Dental X-Ray unit, which adopts a new technology and process. The x ray unit has the advantages of high-efficiency, Clear image, Low leak radiation and easy to carry.

The chargeable battery can shoot 100 times per charge. It is more stable than the external power source in producing X-rays.

TECHNICAL SPECIFICATIONS

Tube Voltage

65kV

Tube Current

2mA

Time Exposure

0.1~2.5s

High pressure generator

40kHz DC

Rated Power

400VA

Focal Spot To Skin Distance

110mm

Focus Spot Size

0.4mm(TOSHIBA)

Charger Input Voltage

AC100V~240V±10%

Input Voltage

25.2V DC

Supply Frequency

50/60Hz±1%

Radiation Leakage

<0.025mGy/h

Battery

24.2V DC

Weight

2.2KG

Dimensions

17cm×13 cm×15cm (L×W×H)

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.