

TECHNICAL DATA SHEET

Cheaper portable oxygen concentrator generator YSOCS-5



Reference photograph. Confirm accessories and configuration in the quotation.

Portable oxygen concentrator generator YSOCS-5

Model

YSOCS-5

Flow rate

1-5L / min, 93% $\pm$ 3%, 10L / min, 90% $\pm$ 2%

Outlet Pressure (Mpa)

0.04-0.07

Sound Level

$\leq$ 50db

Power

AC230V, 50Hz(AC220V/110V $\pm$ 10%, 50/60 $\pm$ 1Hz are available)

Power Consumption

$\leq$ 550W

LCD display

Swit times, Operating pressure, Present Working Time,

Accumulating Time, presetting Time from 10mins to 40hours

Alarm

Power failure alarm, High&Low pressure alarm

Net Weight

26Kgs

Size (mm)

365×375×600mm

Optional:

*Nebulizer(Atomization)

*Low purity alarm: when oxygen purity is above 82%, it will give green light; when the purity is below 82%(82% not included), it will give red light.

*Maintenance alarm: alarm for maintenance after 3000 hours operation

*Alarm for high temperature inside systems above 50°C

*Pulse oximeter: fingertip pulse oximeter is available for monitoring patient oxygen saturation on site.

*Small LCD display: accumulating time; present working time presetting time.

*Dual flows.

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.