

TECHNICAL DATA SHEET

David HKN-90 New Design Infant Radiant Warmer



Reference photograph. Confirm accessories and configuration in the quotation.

New Design Infant Radiant Warmer

Power requirement

AC220V-230V/50Hz or AC110-120V/50-60Hz, 600VA

Control Mode

Pre-warm Mode, Manual Mode and Baby Mode control by micro-computer

Baby Mode temperature control range

34.5-37.5°C

Skin temperature display range

5°C-65°C

Accuracy of skin temperature sensor

±0.2°C

Temperature uniformity of mattress

≤2°C

Angle of heater head

0°, 30°, 45° for two ways

Inclination of the bassinet

Five tilt position

Apnea timer

Audible and visible alarm when the device runs to 50"~1', 4'50"~5', 9'50"~10'

Failure alarm

over temperature alarm, deviation alarm, sensor failure alarm, power failure alarm, setting alarm, checking alarm and so on.

Environmental Requirement

Operating range: 18 °C~30°C

Ambient air velocity rate: <0.3m/s

Product Packaging

Package: The whole unit is packed into one carton

Dimension: 1110mm x 625mm x 1195mm

Gross Weight: 60kg

Product advantage of the Infant Radiant Warmer

- With a warm, hand control, skin temperature three kinds of temperature control mode;
- Set the temperature and skin temperature display;
- Independent over-temperature cut-off device of the triple over-temperature protection;
- Radiation box horizontal angle and the tilt angle adjustable crib;
- Products with self-test function, a variety of fault alarm;
- Cots can be placed under the X-ray film cassette.

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.