

TECHNICAL DATA SHEET

Horizontal cylindrical autoclave sterilizer YSMJ-DC

Horizontal cylindrical autokey sterilizer YSMJ-DC

Characteristics: pressure steam sterilizer

1. Sterilizing course automatic sterilization controlled,easy to operate.
2. With drying function,suitable dressing drying.
3. With over-temperature,over-pressure auto-protect device.
4. The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa.It can't be start on if the door doesn't close well.
- 5.The safety valve will be open automatically when the inner pressure over 0.24MPa,and the steam be exhausting to the water tank.
6. The power will be cut-off automatically,cut-off the water and alarm when the machine lacking water.
7. Fully stainless steel structure.

TECHNICAL DATA: m sterilizer

pressure steam sterilizer

Technical data

YSMJ-DC150

YSMJ-DC200

YSMJ-DC280

YSMJ-DC400

Strilizing chamber

150L

200L

280L

400L

Volume

φ440×850mm

φ515×1000mm

φ600×1000mm

φ700×1100mm

working pressure

0.22MPa

working temperature

134°C

Adjustment of temperature

40°C- 134°C

Time of sterilization

0-99 min

Time of drying

0-99 min

Heat average

$\leq \pm 2^{\circ}\text{C}$

Power

9KW/380V 50Hz

9KW/380V 50Hz

12KW/380V 50Hz

18KW/380V 50Hz

Dimension

1400×600×1300

1400×670×1650

1400×770×1780

1430×880×1830

Transport dimension

1550×750×1850

1560×820×1850

1680×920×2100

1600×1050×2100

G.W/N.W

320/240 KG

350/260 KG

465/365 KG

530/420 KG

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.