

TECHNICAL DATA SHEET

Integrated Multi-function Electric Operating Table YSOT-D3

Integrated Multi-function Electric Operating Table YSOT-D3

YSOT-D3 Integrated Multi-function Electric Operating Table

YSOT-D3 electric operating table is a cost-effective, multi-performance mobile operating table that meets the requirements of different surgeons.

Features

Electro-hydraulic mode of operation is adopted. Two control modes (hand-held remote controller and panel) are available to control various movements. MCU processing is used. Self-locking function is provided to avoid false triggering.

Quality stainless steel 304 is used for table support, base plate, column shield and rails on both sides of the table, easy for cleaning and sterilization. Console supports the use of cast aluminum parts, never rust.

The mattress is wrapped with imported artificial leather. High-density memory sponge is formed in one piece, with no seam.

Imported carbon steel plate is used for the table top, which is convenient for X-ray photography.

AC and DC can use at the same time.

It has the function of auto-restoration.

The table top can sliding

Electric braking device, convenient for shifting the operating table.

Standard Accessories:

A pair of shoulder support frame, a pair of waist support frame, a pair of arm resting frame, a pair of leg support frame, a screen frame, a pair of pedal foot board, a waistband.

TECHNICAL SPECIFICATION:

Table Length (mm) 2000 ± 100

Table Width (mm) 520 ± 20

Height Adjustment (mm) $(700-1100) \pm 50$

Tilt(Left)/Tilt(Right) $\geq 18^\circ$

Trendelenburg/Rev-Trend $\geq 25^\circ / \geq 35^\circ$

Head board Upwards $\geq 50^\circ$

Head board Downwards $\geq 90^\circ$

Backboard Upwards $\geq 70^\circ$

Backboard Downwards $\geq 30^\circ$

Waist board Outwards 100 ± 20

Leg board Upwards $\geq 10^\circ$

Leg board Downwards $\geq 90^\circ$

Leg board Outwards $\geq 180^\circ$

Lumbar upper/lower corner $\leq 150^\circ / \leq 110^\circ$

Horizontal longitudinal 300 ± 30

Main Voltage AC $220V \pm 22V, 50HZ \pm 1HZ$

Input power VA $400 \pm 10\%$

PRODUCT ADVANTAGE:

- 1.Imported Japan hydraulic engine
- 2.Imported electromagnetic valve
- 3.Imported sealing ring
- 4.Ultra-low position for long time operation
- 5.Do X-ray
- 6.leg board are separated & dischargeable
- 7.waist can be lifted
- 7.waist can be lifted

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.