



Wellmed Pro | Wellview Universal Group

TECHNICAL DATA SHEET

Pocket bluetooth ORP tester/meter YSTE-DORP1 Plus

Features

Replaceable combined probe design, meeting different applications

Multi-color backlight display, easy to read data in different modes

Data reading indicator and automatic data locking when the reading is stable

Low voltage indication ensures timely battery replacement

Buffers solutions: CH, USA, NIST standards are selectable

Auto shut-off time, customized backlight display time

Supplied with standard solution, sample vials and lanyard for convenient field test

Dual-control mode with mobile APP connection to achieve powerful data storage

The mobile APP provides four types of measurement display for different situations, including Graph mode, Table mode, Dial mode, and General mode

Protection class: IP67

Parameters

Parameter

mV(ORP).°C

pH Resolution

-

pH Calibration points

-

ORP Measurement range

(-1000.0~+1000.0)mV

ORP Accuracy

± 0.1% F.S ± one digit

Conductivity Resolution

-

Temperature Measurement range

0~60°C(32~140°F)

Calibration reminder

Yes

Timing datalogging

Yes

pH Measurement range

-

pH Accuracy

-

pH ATC range

-

ORP Resolution

0.1/1

Conductivity Measurement range

-

Conductivity Accuracy

-

Temperature Accuracy

±0.2°C

Sample ID Classification

Yes

Operation guider

Yes

Several display models

Yes

Test Kit

Meter;Probe:DORP1-S(pre-installed);

3.0 mol KCl pH/ORP soaking solution:10mL,1 bottle;

Sample Vials:30mL*1;Standard ORP solution:222 mV,30mL;

4X1.5V AAA alkaline batteries(pre-installed);Lanyard;

Hard carrying case(L/W/H:28.0X23.0X8.2cm)

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.