



Wellmed Pro | Wellview Universal Group

TECHNICAL DATA SHEET

Portable Sputum Suction Machine YS-23A2

Portable Sputum Suction Machine YS-23A2

Features:

All-plastic ABS enclosure that is formed in one piece is adopted.

Macromolecule suction bottle is adopted, allowing for cleaning and disinfection.

This device has no oil pump and is maintenance-free.

This device has a small volume and low noise.

This device is equipped with an overflow protection unit to prevent liquid from getting into pump body

TECHNICAL SPECIFICATION:

Power voltage: AC 220V $\pm$ 10% 50Hz

Negative pressure: $\geq$ 0.07Mpa(600mmHg)

Suction rate: $\geq$ 15L/min

Negative pressure range: 0.013-0.07Mpa (600mmHg)

Suction bottle: 1000ml

Input power: 150VA

Pump structure: oil-free self-lubricated pump

Noise: $\leq$ 50dB

Working type: intermittent loading,continuous operation

PRODUCT ADVANTAGES:

imported diaphragm pump

all ABS plastic shell

bottle is easy for cleaning & disinfection

oil-free pump is maintenance-free

small size and low noise

with an overflow protection

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.