

TECHNICAL DATA SHEET

Table Class B Autoclave YSMJ-VRV-B23

Table Class B Autoclave YSMJ-VRV-B23

Features

The accessories of Sterilization include: Sterilization Chamber, Door unit, Insulation unit, Pipe system, Safety valve, Control system, Storage tanks, waste water tank, Steam generator and so on.

3 time pulsating vacuum make less residual air in chamber to Ensure better sterilization effect.

LCD screen show all sterilization data, which ensure better control of the sterilization process

Safety valve installed in sterilizer, when pressure beyond 0.27Mpa. The balance pressure can be released by safety valve to ensure the operate safety.

The instrument have self-protect feature. When water tank or drainage water tank

is full, the sterilization will complete pending sterilization in case the

implementation of sterilization procedures , But the machine can not start to next operation unless add water or drainage. There will be buzzer to remind users to add water or drainage

This product can be applied in the tooth device, operation device, Sanitary

Material and other heat-resisting articles existing in the Dept. of Stomatology,

Ophthalmology Surgery and lab.

Tech. Parameter

Inner chamber of the Sterilizer (Diameter X Depth):

12L:200mm X 360mm 16L: 229mm X 360mm

18L:245mm X 350mm 23L: 245mm X150MM

Sterilizer product size(length*width*height):

23L:660mm X 442mm X 380mm

18L:540mm X 442mm X 380mm

Related Voltage: 220V/50Hz, 110V/60Hz

Related Power: 1800w

Sterilization(Pressure/Temperature):

90~130KPa/121°C(standard atmospheric pressure)

20~230KPa/134°C(standard atmospheric pressure)

Safety Grade: Grade I

Fuse: T15A

Water tank Capacity: 2L

Each cycle water consumption: 0.3L

Minimum tank level alarm: 0.5L

Operate Temperature: 0~40°C

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.