

TECHNICAL DATA SHEET

YS-23C1 Mobile Diaphragm Suction Machine

Mobile diaphragm suction machine YS-23C1

Features:

All-plastic ABS enclosure that is formed in one piece is adopted.

The device is equipped with a imported membrane pump available with long service life.

This device has low noise and is maintenance-free.

This device is equipped with an overflow protection unit to prevent liquid from getting into pump body.

TECHNICAL SPECIFICATION:

Power voltage:

AC220V $\pm$ 10% 50Hz

Negative pressure:

≥ 0.09 MPa(680mmHg)

Suction rate:

≥ 25 L/min(35L pump suitable)

Range of negative pressure:

0.013MPa $\sim$ 0.09Mpa(680mmHg)

Suction bottle:

2500ml x 2

Noise:

≤ 55 dB

Input power:

400VA

Pump structure:

Diaphragm type

Working type:

intermittent loading,continuous operation

PRODUCT ADVANTAGES:

1.imported diaphragm pump

2.all ABS plastic shell

3.bottle is easy for cleaning & disinfection

4.oil-free pump is maintenance-free

5.low noise

6.with an overflow protection

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.