



Wellmed Pro | Wellview Universal Group

TECHNICAL DATA SHEET

YSTE-DPH10 Portable color screen single parameter pH meter/tester

Features

3.5" TFT Color Display, easy to read

The new UI interface, easy operation

Intelligent function with Auto. timing datalogger, parameter setting, data holder

Data storage up to 3000 groups

Cond mode: Support probe constant calibration, conductivity standard solution calibration

Power supply: rechargeable lithium battery/USB

Charging socket: USB/Type-C, in line with the European new regulations.

Protection class: IP57

Parameters

Parameter

pH/mV.°C | mV(ORP).°C

pH Resolution

0.1/0.01/0.001

pH Calibration points

1, 2, -3pts automatic

ORP Measurement range

(-1999.9~+1999.9) mV

ORP Accuracy

± 0.03% F.S ± one digit

Conductivity Calibration points

-

Conductivity ATC range

-

OJ Measurement range

-

pH Measurement range

(-2.000~20.000) pH

pH Accuracy

± 0.002pH ± one digit

pH ATC range

(0.0~100.0) °C/(32.0~212.0)°F

ORP Resolution

0.1/1

Conductivity Measurement range

-

Conductivity Resolution

-

Conductivity Accuracy

-

DO Accuracy

-

O saturation

-

DO Automatic barometric pressure compensation

-

DO Automatic temperature compensation

-

Temperature Measurement range

(0.0~100.0) °C/(32.0~212.0)°F

Charging socket

Type-C

DO Manual salinity compensation

-

Temperature Accuracy

±0.2°C

Power supply

Rechargeable lithium battery

IP Rating

IP57

Test kit

Meter;Plastic ATC pH probe D201T-H;

pH buffer solution:pH4.00/7.00/10.01,50mL,one for each;

Rechargeable lithium battery(pre-installed);

Charging cable: 1pc;

Hard carrying case(L/W/H: 33.0x27.8x8.2cm):1pc

Panama | Central America | Caribbean | CARICOM

Information from the authorized catalog. Confirm configuration, accessories and documentation in the quotation.

Assisted translation: review the manufacturer specifications before purchasing.